

## CJX3 series Modular Contactor

### APPLICATION

CJX3 series modular contactor is mainly used for the electric power system with AC 50Hz (or 60Hz) and rated working voltage up to 400V. Under the using category of AC-7a, the product can serve for remote switch and master circuit control in the circuit with rated working voltage up to 400V and rated working current up to 63A.

This product can be used for loading control of household electrical appliance and low induction loading and household motor with similar usages.



CJX3-20 2P



CJX3-40 2P



CJX3-20 4P

### SPECIFICATION

AC-1/AC-7A swithing of heaters	CJX3 20	CJX3 25	CJX3 40	CJX3 63
Rated operation current Ie(NO)	20A	25A	40A	63A
Rated operation current Ie(NC)	20A	25A	30A	30A
Rated operation power(NO)				

230V Single-phase	4.0KW	5.3KW	8.8KW	13.8KW
230V Three-phase	-	9KW	15.2KW	24KW
400V Three-phase	-	16KW	26KW	41KW

### AC-3/AC-7B switching motors

Rated operation current Ie(NO)	9A	9A	22A	30A
Rated operation current Ie(NC)	9A	6A	-	-
Rated operation power(NO)				
230V Single-phase	1.3KW	1.3KW	3.7KW	5KW
230V Two-phase	-	2.2KW	5.5KW	8KW
400V Four-phase	-	4KW	11KW	15KW

### DESCRIPTION

Weight: ≤125g

Environmental temperature: -5℃~+40℃

Mechanical lifetime: not less than 1x10<sup>5</sup> times

Electric lifetime: not less than 3x10<sup>4</sup> times

### DIMENSIONS

